

Christie CDA2 Professional power amplifier

2000W in a sleek, efficient and powerful Class D design

Ideal for cinema audio applications, the Christie® CDA2 professional power amplifier utilizes an advanced high-speed Class D architecture and high current switch mode power supply. It offers high-power output and efficiency with very low heat output and fast transient response and stability, even with low impedance loads. Featuring two fully independent channels, with operation in parallel, stereo and bridged modes, the Christie CDA2 handles a range of demanding applications with ease.



Key features

- | | |
|---|--|
| Class D architecture | 540W per channel at 4 ohms
@ <0.1% THD |
| High-power output, high efficiency
and stable performance | Switch mode power supply |
| Two channels of independent,
fourth-order 100Hz crossovers | Neutrik XLR/TRS 1/4" inputs,
balanced +4dB professional level |
| Active, Signal Present, DC Protection
and Thermal LED indicators | Neutrik Speakon high current
locking output connectors |
| Parallel/Bridge/Stereo mode switch | Limited three year warranty |
| Stepped input level controls | |

CHRISTIE®
VIVE AUDIO

Reliability and quality built in

Designed for long-term continuous operation, the Christie CDA2 features high quality components, including extra large capacitors and inductors, automatic clip limiting circuitry and DC voltage protection with LED status indicators to prevent damage to speakers.



Specifications		
Rated power	bridge 4 ohms	• 1960W @ 1kHz 1% T.H.D.
	bridge 8 ohms	• 1160W @ 1kHz 1% T.H.D.
	2 x 2 ohms	• 980W per channel @ 1kHz 1% T.H.D. both channels driven
	2 x 4 ohms	• 540W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	2 x 8 ohms	• 275W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	1 x 2 ohms	• 1050W @ 1kHz at <0.1% T.H.D.
	1 x 4 ohms	• 600W @ 1kHz at <0.1% T.H.D.
	1 x 8 ohms	• 290W @ 1kHz at <0.1% T.H.D.
Minimum load impedance	• 2 ohms	
Maximum RMS voltage swing	• 56V	
Frequency response	• 10Hz-45kHz; +0, -3dB @ 1W	
T.H.D.	2 x 2 ohms	• <0.1% @ 800W per channel from 20Hz-10kHz, decreasing to 760W @ 20kHz
	2 x 4 ohms	• <0.1% @ 500W per channel from 20Hz-20kHz
	2 x 8 ohms	• <0.1% @ 270W per channel from 20Hz-20kHz
Input CMRR	• >-77dB @ 1kHz	
Voltage gain	• x 60 (+35dB)	
Crossover	• 100Hz switchable 2nd order high pass and 3rd order low pass per channel	
Crosstalk	• >-70dB @ 1kHz at 100W power @ 4 ohms	
Hum and noise	• >-100dB, "A" weighted referenced to rated power @ 4 ohms	
Slew rate	• >12V/μs	
Damping factor (8 ohms)	• >250:1 @ 20Hz-1kHz @ 8 ohms	
Phase response	• +6° to -70° from 20Hz-20kHz	
Input sensitivity	• 0.775V ±3% for 1kHz 4 ohm rated power • 0.735V ± 3% for 1kHz 2 ohm rated power	
Input impedance	• 15k ohms balanced • 7.5k ohms unbalanced	
Current draw	@ 1/8 power	• 620W @ 2 ohms • 390W @ 4 ohms • 250W @ 8 ohms
	@ 1/3 power	• 1250W @ 2 ohms • 810W @ 4 ohms • 460W @ 8 ohms
Cooling	• Temperature dependent variable speed 80mm DC fan	
Controls	• 2 front panel attenuators • Crossover select switch for H.P.F, Normal and L.P.F	
	• Input mode switch for Stereo, Bridge and Parallel	
Indicator LEDs	• 2 DDT (ACL clip limiting) • 2 signal presence • 2 active status • 2 temp • 2 DC protect	
Protection	• Thermal • DC • Subsonic • Incorrect loads • Under and over voltage	
Connectors	inputs	• Neutrik Dual Combi 1/4" XLR
	outputs	• Three Neutrik Speakon connectors for two channels plus common bridge
Construction	• 18 ga. galvanized steel	
Dimensions	• (LxWxH) 10.5 x 19 x 3.5" (266 x 482 x 89mm) behind front panel + 0.6" for handle • 2 RU mounting	
Net weight	• 10.90lbs (4.94kg) ¹	
Gross weight	• 13.3lbs (6.02kg)	
Warranty	• Limited three year warranty	

Rated power readings made with BW: <10Hz-22kHz. All power measurements made at 120 VAC.

2 ohm power is time limited by circuit breaker.

Input power requirements: 120 VAC, 60Hz, 5A.

¹ Net weight does not include power cord.

Corporate offices

Christie Digital Systems USA, Inc.
USA – Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Canada – Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3844 9514

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6278 7708

Eastern Europe and
Russian Federation
ph: +36 (0) 1 47 48 100

France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540

India
ph: +91 (080) 6708 9999

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Republic of South Africa
ph: +27 (0)11 510 0094

Singapore
ph: +65 6877 8737

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000

**Independent sales
consultant offices**

Italy
ph: +39 (0) 2 9902 1161



Kitchener, Ontario

For the most current specification information, please visit www.christiedigital.com

Copyright 2013 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 3566 Jul 13

CHRISTIE