



The Perfect Experience

# 24" Native HD Multi-Format Studio Monitor DT-V24L3D



**Achieving HD images, faithful to original signals, with less than one frame of latency**

### Features

- 1920x1200 pixels
- Circuits that deliver low latency of less than one frame
- Waveform monitoring with over level function
- Gold-plated HD/SD SDI terminals with embedded audio
- DVI-D with HDCP terminal
- High-performance LCD panel
- Exclusive JVC image processing technology
- Status display in unused section of 16:10 panel
- Wide selection of video production functions
- Easy-to-operate front panel controls
- Rugged, adjustable stand provided
- Source ID input by ASCII code
- Information position selectable
- Full screen mode for SD 4:3 signal

### Status Display



\*Information can be displayed in the upper or the lower blank area.

### Input Format

VIDEO	Input terminals				COMPUTER	Input terminals
	Video	Component/RGB	HD/SD SDI	DVI-D with HDCP (video)		
NTSC	✓	—	—	—	VGA60	✓
PAL	✓	—	—	—	W-VGA60	✓
BW(50Hz/60Hz)	✓	—	—	—	SVGA60	✓
480/60i	✓	✓	✓	✓	XGA60	✓
576/50i	✓	✓	✓	✓	W-XGA60 (1280 x 768)	✓
480/60p	✓	✓	✓	✓	W-XGA+60 (1440 x 900)	✓
576/50p	✓	✓	✓	✓	SXGA60 (1280 x 1024)	✓
640 x 480/60p	✓	✓	✓	✓	1920 x 1080@60/50	✓
720/24p, 25p, 30p	✓	✓	✓	✓	1280 x 720@60/50	✓
720/50p, 60p	✓	✓	✓	✓	W-SXGA+60 (1680 x 1050)	✓
1080/50i, 60i	✓	✓	✓	✓	U-XGA60 (1600 x 1200)	✓
1080/50p, 60p	✓	✓	✓	✓	W-LXGA60 (1920 x 1200)	✓
1035/60i	—	✓ <sup>1)</sup>	✓	✓ <sup>1)</sup>	—	—
1080/24p, 25p, 30p	—	✓	✓	—	—	—
1080/24psf, 30psf <sup>1)</sup>	—	✓	✓	—	—	—

<sup>1)</sup> It is displayed by 1080/60i.

### Front Panel




### Specifications

		DT-V24L3D
Model Type		Multi-format HDTV/SDTV LCD monitor
Screen Size		Type 24 wide format
Aspect Ratio		16:10
LCD Panel		24" wide, active matrix TFT
Effective Screen Size (W x H)		51.84 x 32.4 cm
Pixels		1920 x 1200 (W-UXGA)
Display Colours		16.7 million
Viewing Angle	Horizontal	176°
	Vertical	176°
Brightness		400 cd/m <sup>2</sup>
Contrast Ratio		1000:1
Horizontal/Vertical Frequency (PC signals)	Horizontal	31.469 kHz to 75.000 kHz
	Vertical	60 Hz ± 5 Hz
Applicable Standard		Depending on the signal within the range of these frequencies, some signals may not be displayable, in which case, "Out of range" is shown. HD SDI: BTA S-004B, SMPTE292M SD SDI: ITU-R BT.656: 525/625, SMPTE259M: 525 EMBEDDED AUDIO: SMPTE293M, SMPTE272M
Audio Output		Internal: 1.0 W + 1.0 W (L/R)
Environmental Conditions	Operating temperature	5°C to 35°C
	Operating humidity	20% to 80% (non condensing)
Power Requirements		AC 120/220-240 V, 50/60 Hz
Rated Current	1.15 A (AC 120V)	
	0.67 A (AC 220-240 V)	
Dimensions (WxHxD) excluding protrusions	With desktop stand	564 x 448.6 x 243 mm
	Without stand	564 x 408 x 99 mm
Weight	Excluding stand	8.7 kg
	Including stand	11.6 kg
Provided Accessories		AC power cord, power cord holder, screw x 2 (for power cord holder) Protective screen

### Input/Output Terminals

Video	VIDEO 1	Composite video signal input/output: 1 line, BNC x 2, 1 V (p-p), 75 ohms (IN and OUT are connected with a bridge connection) (auto termination)
	VIDEO 2	(IN and OUT are connected with a bridge connection) (auto termination)
	DVI-D (HDCP)	DVI-D signal input (compatible with HDCP): DVI-D connector x 1 (compatible with DDC2B)
	COMPO./RGB (G/Y, B/Pb/B-Y, R/Pr/R-Y)	Analogue component signal/ analogue RGB signal input/output: 1 line, BNC x 6 Video signal: G/Y: 1 V (p-p), 75 ohms (sync signal included), B/Pb/B-Y, R/Pr/R-Y: 0.7 V (p-p), 75 ohms (IN and OUT are connected with a bridge connection) (auto termination)
	EXT. SYNC (CS)	Composite sync signal input/output: 1 line, BNC x 2, 0.3 V (p-p) to 4 V (p-p), 75 ohms (bipolar tri-signal, negative pole binary signals, BB) (video signals excluded) (IN and OUT are connected with a bridge connection) (auto termination)
	HD/SD SDI (IN 1)	Digital signal input (compatible with EMBEDDED AUDIO): Auto detection, 1 line, BNC x 1
	HD/SD SDI (IN 2)	
	HD/SD SDI (OUT)	Digital signal output (compatible with EMBEDDED AUDIO) 1 line (switched output), BNC x 1
Audio	AUDIO ASSIGN (IN 1)	Analogue audio signal input:
	AUDIO ASSIGN (IN 2)	1 line, RCA x 2, 500 mV (rms), high impedance
	AUDIO ASSIGN (MONITOR OUT)	Analogue audio signal output: 1 line, RCA x 2, 500 mV (rms)
External Control	MAKE/TRIGGER	RJ-45 x 1 (8-pin)
	RS-485	RJ-45 x 2 (IN/OUT) (8-pin)
	RS-232C	D-sub (9-pin) x 1

### Dimensions



Option ■ TS-W24F1 (Protective screen)

INPUT TERMINALS	HD/SD-SDI Gold-plated
	DVI-D
	Audio In/Out
CONTROLS	Speaker Stereo
	RS-232C
	RS-485 In/Out
FUNCTIONS	Make/trigger
	Area marker
	Safety marker
	Tally lamp
	Time code
	CRC error
	Audio level meter
	Source ID display
	1:1 mode
	I/P mode
Waveform monitoring	
INSTALLATION	Stand (Tilt & height adjustable)
	VESA
OPERATION	Power AC

### Rear Panel

